

Pottorff Quick Ship Program

Category	Series	Maximum Quantity			Minimum Charge			Options and Accessories
		24 Hr	3-Day	7-Day	24 Hr	3-Day	7-Day	
Fire Dampers	VFD-10, VFD-30	5*	10*	25*	35%	20%	10%	16, 18 & 20 GA. A, B or C Sleeves, Round Duct Transitions, Stainless Steel , Retaining Angles, Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	VFD-10-IS, VFD-30-IS	10*	25*	50*	35%	20%	10%	20 GA. A or B Sleeves, Round Duct Transitions, Retaining Angles, Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	VFD-10-TL	5*	5*	15*	35%	20%	10%	16 & 20 GA. A or B sleeves, Round Duct Transitions, Retaining Angles, Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances.
	VFD-10-IM	5	10	15	35%	20%	10%	20 GA. A or B sleeves, Round Duct Transitions, Retaining Angles, Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances.
	VFD-10D	5*	5*	10*	35%	20%	10%	4000 fpm, 16, 18 & 20 GA. A, B or C Sleeves, Round Duct Transitions, Stainless Steel , Retaining Angles, Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	VFD-15R, VFD-35R	5	10	25	35%	20%	10%	16 & 20 GA. Sleeves. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	VFD-15R-IS, VFD-35R-IS	5	10	25	35%	20%	10%	20 GA. Sleeves. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	FD-140 (OP), FD-150 (OP), FD-340	5*	10*	20*	35%	20%	10%	20 GA. Sleeves, Round Duct Transitions, Stainless Steel , Retaining Angles, Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
Fire/Smoke Dampers	FSD-141, 142, 151, 152, (OP), (SP)	5*	10*	20*	35%	20%	10%	Side Plate, 20 GA. Sleeves, No Sleeve, Round Duct Transitions, Retaining Angles, Net OD dimensions, Stock Actuators, PI-50, Duct Mounted Smoke Detector and Loose Smoke Detector (except model 2151-24V). Varying fuse link temps, sleeve lengths and clearances, DRS-30.
	FSD-171 (OP), FSD-172 (OP)	5	10	20	35%	20%	10%	20 GA. Sleeves, Round Duct Transitions, Stock Actuators, PI-50, Duct Mounted Smoke Detector and Loose Smoke Detector (except model 2151-24V), DRS-30.
	FSD-341, 342	5*	10*	15*	35%	20%	10%	Side Plate, 20 GA. Sleeves, No Sleeve, Round Duct Transitions, Retaining Angles, Net OD dimensions, Stock Actuators, PI-50, Duct Mounted Smoke Detector and Loose Smoke Detector (except model 2151-24V). Varying fuse link temps, sleeve lengths and clearances, DRS-30.
	FSD-125R	5	5	20	35%	20%	10%	Varying fuse link temps, Stock Actuators, DRS-30.
	SD-141, 142, 151, 152	5*	10*	20*	35%	20%	10%	Side Plate, 20 GA. Sleeves, No Sleeve, Round Duct Transitions, Retaining Angles, Net OD dimensions, Stock Actuators, PI-50, Duct Mounted Smoke Detector and Loose Smoke Detector (except model 2151-24V). Varying sleeve lengths and clearances.
	SD-25R	5	10	50	35%	20%	10%	Stock Actuators.
Ceiling Radiation Dampers	CFD-15R	10	20	50	35%	20%	10%	22 GA Sleeves, VC-165, CRB-24, WHI-20, Varying sleeve lengths.
	CFD-15 (No Round Transitions)	15	30	50	35%	20%	10%	22 GA Sleeves, Flange Transition, VC-165, CRB-24, WHI-20, All Plaster Ground Connections, Varying sleeve lengths.
	CFD-15 (With Round Transitions)	10	20	50	35%	20%	10%	22 GA Sleeves, VC-165, CRB-24, WHI-20, All Plaster Ground Connections, Varying sleeve lengths.
	CFD-521 (IP)	-	25	50	-	20%	10%	Round Transitions, VC-165, WHI-20, All Plaster Ground Connections, Boot Rails.
	CFD-521-BT	-	30	70	-	20%	10%	VC-165, WHI-20, All Plaster Ground Connections, Boot Rails.
	CFD-20	5	15	30	35%	20%	10%	22 GA Sleeves, Round Duct Transitions, CRB-24, WHI-20, All Plaster Ground Connections, Varying sleeve lengths.
Air Control Dampers	CD-10R	10	40	100	35%	20%	10%	22 GA. Sleeves, Standoff, Stainless Steel , Varying sleeve lengths and clearances, Locking quadrants.
	CD-10	10	20	40	35%	20%	10%	22 GA. Sleeves, Standoff, Locking quadrants.
	CD-21R, 22R	-	-	20	-	-	10%	Low Leakage Seals, Stock Actuators, Stainless Steel , Varying sleeve lengths.
	CD-25R	10	20	50	35%	20%	10%	Low Leakage Seals, Stock Actuators, Stainless Steel , Varying sleeve lengths, Locking quadrants.
	CD-41, 42, 45, 46	5*	15*	20*	35%	20%	10%	Low Leakage Seals, Locking quadrants, Stock Actuators, 20 GA. Sleeves, Stainless Steel , Side Plates, Net OD dimensions, Varying sleeve lengths and clearances.
	CD-51, 52	-	5*	10*	-	20%	10%	Low Leakage Seals, Locking quadrants, Stock Actuators, 20 GA. Sleeves, Side Plates, Net OD dimensions, Varying sleeve lengths and clearances.
	MD-41, 42	5*	15*	20*	35%	20%	10%	Stand-Off, Locking quadrant, Net OD dimensions.
Backdraft Dampers	BD-20R (Catalog sizes only)	-	50	100	-	20%	10%	
	BD-50, 54	10*	20*	60*	35%	20%	10%	B or C Mounting Flange, Net OD dimensions, Varying sleeve lengths- 20 ga. only.
	BD-60, 64	5*	10*	20*	35%	20%	10%	B or C Mounting Flange, Stainless Steel , Net OD dimensions, Varying sleeve lengths- 20 ga. only. Neoprene blade edge seals.
	SFD-445, SFD-635, SFJ-445, SFJ-645	-	5*	10*	-	20%	10%	Integral Flange Frame (Mech. Fastened Only), Standard head and sill flashing, Net OD dimensions, Clip and continuous angles.

Pottorff Quick Ship Program

Category	Series	Maximum Quantity			Minimum Charge			Options and Accessories
		24 Hr	3-Day	7-Day	24 Hr	3-Day	7-Day	
Louvers Standard paint extends the Quick Ship Program by 3 days. Anodize extends program by 10 days	EFD-245, EFJ-245, EFJ-430, EFJ-437, EFJ-645, EFK-430, EFK-437, EFK-445, EFK-637	≤25 sq. ft	≤100 sq. ft	≤125 sq. ft	35%	20%	10%	Integral Flange Frame (Mech. Fastened Only), Standard head and sill flashing, Net OD dimensions, Clip and continuous angles.
	EFD-435, EFD-445, EFD-645, EFD-437	≤25 sq. ft	≤100 sq. ft	≤250 sq. ft	35%	20%	10%	Integral Flange Frame (Mech. Fastened Only), Standard head and sill flashing, Net OD dimensions, Clip and continuous angles.
	EFJ-637, EFJ-445	≤ 25 sq. ft	≤ 100 sq. ft	≤ 150 sq. ft	35%	20%	10%	Integral Flange Frame (Mech. Fastened Only), Standard head and sill flashing, Net OD dimensions, Clip and continuous angles.
	EFJ-637-HP, EFY-245, EFY-445	≤ 25 sq. ft	≤ 100 sq. ft	≤ 150 sq. ft	35%	20%	10%	Integral Flange Frame (Mech. Fastened Only), Standard head and sill flashing, Net OD dimensions, Clip and continuous angles.
	ECD-545, ECD-545-MD, EFD-637-MD	≤25 sq. ft	≤50 sq. ft	≤100 sq. ft	35%	20%	10%	Integral Flange Frame (Mech. Fastened Only), Net OD dimensions, Sieved.
	ECD-635	-	≤ 25 sq. ft	≤ 50 sq. ft	-	20%	10%	Integral Flange Frame (Mech. Fastened Only), Standard head and sill flashing, Net OD dimensions, Clip and continuous angles.
	ECD-745	-	≤ 25 sq. ft	≤ 50 sq. ft	-	20%	10%	Standard head and sill flashing, Net OD dimensions, Clip and continuous angles.
	EBE-445, EBI-445	-	≤ 25 sq. ft	≤ 50 sq. ft	-	20%	10%	Integral Flange Frame (Mech. Fastened Only), Standard head and sill flashing, Net OD dimensions, Clip and continuous angles.
EOD-445, EOD-637, EOJ-445, EOJ-637, EXD-437, EXD-645	-	≤ 25 sq. ft	≤ 50 sq. ft	-	20%	10%	Stock Actuators, Integral Flange Frame (Mech. Fastened Only), Standard head & sill flashing, Net OD dimensions, Clip & continuous angles, Jamb & blade seals.	
Standard paint extends the Quick Ship Program by 7 days. Anodize extends program by 14 days.	EBV-145, EBV-445 (Catalog Sizes Only)	-	49	150	-	20%	10%	
Access Doors	HAD, CAD (Catalog sizes only)	10	25	100	35%	20%	10%	
	RAD (Catalog sizes only)	10	25	100	35%	20%	10%	
	WAD, OAD	-	5	15	-	20%	10%	
	DM, DMR (Catalog sizes only)	-	20	40	-	20%	10%	
	DMHT-2300 (Catalog sizes only)	-	5	10	-	20%	10%	

Note: * denotes Single Sections. 1/2 quantities are available for two sections. 1/3 quantities available for 3 sections. Please contact the factory for special requirements. Items shown in Bold are only available on the 7-day program. 24 Hr, 3 Day and 7 Day Quick Ship: Orders received before 12:00 Noon Central Time will ship the next business day, 3 days or 7 days respectively. Orders received after 12:00 Noon Central Time will ship in 2 days, 4 days, or 8 days respectively.