









Category	Product	Location	Maximum Qty			Options and Accessories
			24hr	3-Day	7-Day	
<b>Fire Dampers</b> 	VFD-10, VFD-30	TX, CA	50*	100*	200*	Retaining angles. Net OD dimensions. Varying fuse link temps. Horizontal and vertical applications.
	VFD-10, VFD-30	TX, CA	25*	50*	100*	16, 18 & 20 GA. A, B or C sleeves. Round, flanged and DM-35 duct transition. <b>Stainless Steel.</b> Retaining angles. Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	VFD-10-IS, VFD-30-IS	TX, CA	50*	100*	200*	20 GA. A, or B sleeves. Round, flanged and DM-35 duct transitions. Retaining angles. Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	VFD-10-TL, VFD-10D-TL	TX, CA	5*	5*	15*	16, 18 & 20 GA. A, or B sleeves. Round, flanged and DM-35 duct transitions. Retaining angles, Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	VFD-10-IM	TX, CA	50	100	200	20 GA. A, or B sleeves. Round, flanged and DM-35 duct transitions. Retaining angles. Net OD dimensions. Varying fuse link temps and clearances. Horizontal and vertical applications.
	VFD-10D	TX, CA	50*	100*	200*	4000 fpm, 16, 18 & 20 GA. A or B sleeves. Round, flanged and DM-35 duct transitions. <b>Stainless steel.</b> Retaining angles. Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horiz. and vert. app.
	VFD-10D	TX, CA	-	100*	200*	4000 fpm, 16, 18 & 20 GA. A, B or C sleeves. Round, flanged and DM-35 duct transitions. <b>Stainless steel.</b> Retaining angles. Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horiz. and vert. app.
	VFD-30D	TX, CA	50*	100*	200*	4000 fpm, 16, 18 & 20 GA. A or B sleeves. Round, flanged and DM-35 duct transitions. <b>Stainless steel.</b> Retaining angles. Net OD dimensions. Varying fuse link temps, sleeve lengths and clearances. Horiz. and vert. app.
	VFD-15R, VFD-35R	CA	5	10	25	16 & 20 GA. sleeves. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	VFD-15R-IS, VFD-35R-IS	CA	5	10	25	20 GA. sleeves. Varying fuse link temps, sleeve lengths and clearances. Horizontal and vertical applications.
	FD-125R	CA	15	20	30	Varying fuse link temps.
	FD-140 (OP), FD-150 (OP), FD-340	TX, CA	15*	20*	30*	16, 18 & 20 GA. sleeves. Round, flanged and DM-35 duct transitions. Horizontal and vertical applications.
<b>Fire/Smoke Dampers</b> 	FSD-141, 142, 143, (OP), (SP)	TX, CA	15*	20*	30*	Side plate. 16, 18 & 20 GA. sleeves. No sleeves. Round, flanged and DM-35 duct transitions. <b>Stainless steel.</b> Retaining angles. Net OD dimensions. Stock actuators. PI-50. Duct mounted smoke detector (3-day, maximum of 5 units or 7-day only) and loose smoke detector. Varying fuse link temps, sleeve lengths and clearances. DRS-30, RCP-1, RCP-1K, RCP-1M and RCP-1M-NL.
	FSD-151, 152, (OP), (SP)	CA				
	FSD-171 (OP), FSD-172 (OP)	TX, CA	15	20	30	16, 18 & 20 GA. sleeves. Round, flanged and DM-35 duct transitions. <b>Stainless steel.</b> Stock actuators. PI-50. Duct mounted smoke detector (3-day, maximum of 5 units or 7-day only) and loose smoke detector. DRS-30, RCP-1, RCP-1K, RCP-1M and RCP-1M-NL.
	FSD-341, 342, 351, 352	TX, CA	15*	20*	30*	Side plate. 16, 18 & 20 GA. sleeves. No sleeves. Round, flanged and DM-35 duct transitions. Retaining angles. Net OD dimensions. Stock actuators. PI-50. Duct mounted smoke detector (3-day, maximum of 5 units or 7-day only) and loose smoke detector. Varying fuse link temps, sleeve lengths and clearances. DRS-30, RCP-1, RCP-1K, RCP-1M and RCP-1M-NL.
	FSD-125R	CA	15	20	30	Varying fuse link temps. Stock actuators. DRS-30, Horizontal mount, RCP-1, RCP-1K, RCP-1M and RCP-1M-NL.
	SD-141, 142	TX, CA	15*	20*	30*	Side Plate, 16, 18 & 20 GA. sleeves. No sleeves. Round, flanged and DM-35 duct transitions. <b>Stainless steel.</b> Retaining angles. Net OD dimensions. Stock actuators. PI-50. Duct mounted smoke detector (3-day, maximum of 5 units or 7-day only) and loose smoke detector. Varying sleeve lengths and clearances. DRS-30, RCP-1, RCP-1K, RCP-1M and RCP-1M-NL.
	SD-151, 152	CA				
	SD-25R	CA	15	20	30	Stock actuators. RCP-1, RCP-1K, RCP-1M and RCP-1M-NL.
<b>Ceiling Radiation Dampers</b> 	CFD-15R	TX, CA	50	100	200	CRB-24, WHI-20.
	CFD-15R	TX, CA	25	50	100	22 GA sleeves. VC-165, CRB-24, WHI-20. Varying sleeve lengths.
	CFD-15 (No Round Transitions)	TX, CA	50	100	200	22 GA. sleeves. Flange transition. VC-165, CRB-24, WHI-20. All plaster ground connections. Varying sleeve lengths.
	CFD-15 (With Round Transitions)	TX, CA	-	20	50	22 GA. sleeves. Flange transition. VC-165, CRB-24, WHI-20. All plaster ground connections. Varying sleeve lengths.
	CFD-521 (NP)	TX	50	100	200	Round transitions (mounted or loose). VC-165, WHI-20. All plaster ground connections. Boot rails.
	CFD-521-IP	TX	50	100	200	VC-165, WHI-20. All plaster ground connections. Boot rails.
	CFD-521-IP	TX	-	-	30	Round transitions (mounted or loose). VC-165, WHI-20. All plaster ground connections. Boot rails.
	CFD-20	TX, CA	30	60	120	22 GA sleeves. Round duct transitions. CRB-24, WHI-20. All plaster ground connections. Varying sleeve lengths.

			Maximum Qty			
Category	Product	Location	24hr	3-Day	7-Day	Options and Accessories
<b>Air Control Dampers</b> 	CD-10R	CA	30	80	200	22 GA. Sleeves. Standoff. <b>Stainless steel</b> . Varying sleeve lengths and clearances. Locking quadrants.
	CD-10	CA	30	60	120	22 GA. Sleeves. Standoff. Locking quadrants.
	CD-21R	CA	30	60	150	Low leakage seals. Stock actuators. <b>Stainless steel</b> . Varying sleeve lengths. Standoff brackets.
	CD-25R	CA	30	60	150	Low leakage seals. Stock actuators. <b>Stainless steel</b> . Varying sleeve lengths. Locking quadrants. Standoff brackets.
	CD-41, 42, 45, 46	TX, CA	15*	45*	60*	Low leakage seals. Locking quadrants. Stock actuators. 16, 18 and 20 GA. Sleeves. Round. Flanged. DM-35 duct transitions. <b>Stainless steel</b> . Side plates. Net OD dimensions. Varying sleeve lengths and clearances. Standoff. Vertical blades. Stainless steel bushings. PI-50.
	CD-51, 52	TX, CA	-	20*	50*	Low leakage seals. Locking quadrants. Stock actuators. 18, 18 and 20 GA. Sleeves. Round. Flanged. DM-35 duct transitions. Side plates. New OD dimensions. Varying sleeve lengths and clearances. Standoff. Vertical blades. Stainless steel bushings. PI-50.
	MD-41, 42	TX, CA	15*	45*	60*	Standoff. Locking quadrant. Net OD dimensions. No top/bottom stops. Stainless steel bushings.
<b>Backdraft Dampers</b> 	BD-20R (catalog sizes only)	TX, CA	-	-	100	
	BD-150, 250	TX	30*	60*	120*	B (Discharge) or C (Intake) mounting flange. Net OD dimensions.
	BD-150, 250 (with sleeves and/or Stock actuators)	TX	-	10*	20*	B (Discharge) or C (Intake) mounting flange. New OD dimensions. Varying sleeve lengths and clearances. 16, 18 and 20 GA. Stock actuators.
	CBD-150, 250	TX	30*	60*	120*	B (Discharge) or C (Intake) mounting flange. New OD dimensions. Vertical or horizontal. Airflow up mount.
	CBD-150, 250 (with sleeves)	TX	-	10*	20*	B (Discharge) or C (Intake) mounting flange. New OD dimensions. Varying sleeve lengths and clearances. 16, 18 and 20 GA. Stock actuators.
	BD-51	TX	10*	20*	60*	B or C mounting flange. New OD dimensions. Varying sleeve lengths and clearances. 16, 18 and 20 GA.
<b>Louvers</b> (Standard paint extends the Quick Ship Program by 2 days) 	SFD-445/635, SFJ-445/645	CA	-	5*	10*	Integral flange frame (mechanically fastened only). Standard head and sill flashing. New OD dimensions. Clip and continuous angles. No screen. Insect screen - aluminum (18-16 mesh).
	ECD-245/445/545/635 EDD-445/637 EFD-245/435/437/445/637/645 EFJ 430/437/445, EFK-430/437/445 EFJ-437-HP, EFJ-637-HP	TX	≤50 sq. ft.	≤175 sq. ft.	≤250 sq. ft.	Integral flange frame (mechanically fastened only). Standard head and sill flashing. Net OD dimensions. Clip and continuous angles. Screen location - front/exterior. No screen. Insect screen - aluminum (18-14 mesh). Insect screen - aluminum (18-16 mesh). Bird screen - galvanized (1/2" x 19 GA.). Insect screen - stainless steel (18-16 mesh). Florida Building Code construction. Custom flange (n/a for 24 hour). Stucco and glazing frame - match louver. Frame only - match louver. Filter rack. Blankoff. <b>Burglar bars</b> .
	EFJ-937-MD, EXA-645-MD	TX	-	-	≤50 sq. ft.	
	EFD-635/EFY-245/445 EFJ-245/645/EFK-637/645	TX	≤25 sq. ft.	≤100 sq. ft.	≤150 sq. ft.	
	EFD-637-MD	TX	≤25 sq. ft.	≤50 sq. ft.	≤100 sq. ft.	Integral flange frame (mechanically fastened only). Standard head and sill flashing. Net OD dimensions. Clip and continuous angles. Sleeved (n/a for 24 hour). Screen location - Front/exterior. No screen. Insect Screen - aluminum (18-14 mesh). Insect screen - aluminum (18-16 mesh). Bird screen - galvanized (1/2" x 19 GA.). Insect screen - stainless steel (18-16 mesh). Florida Building Code construction. Custom flanges (n/a for 24 hour). Stucco and glazing frame. Screen and frame - match louver. Frame only - match louver. Filter rack. Blankoff. <b>Burglar bars</b> .

			Maximum Qty			
Category	Product	Location	24hr	3-Day	7-Day	Options and Accessories
<b>Louvers</b> (Standard paint extends the Quick Ship Program by 2 days) 	<b>ECD-545-MD</b>	<b>TX</b>	-	-	<b>≤100 sq. ft.</b>	Integral flange frame (mechanically fastened only). Standard head and sill flashing. Net OD dimensions. Clip and continuous angles. Sleeved. Screen location - Front/exterior. No screen. Insect Screen - aluminum (18-14 mesh). Insect screen - aluminum (18-16 mesh). Bird screen - galvanized (1/2" x 19 GA.) Insect screen - stainless steel (18-16 mesh). Custom flanges (n/a for 24 hour). Stucco and glazing frame. Screen and frame - match louver. Frame only - match louver. Filter rack. Blankoff. <b>Burglar bars.</b>
	<b>EEl-430, EFE-430-HP</b>	<b>TX</b>	-	<b>≤25 sq. ft.</b>	<b>≤50 sq. ft.</b>	Integral flange frame (mechanically fastened only). Standard head and sill flashing. Net OD dimensions. Clip and continuous angles. Screen location - Front/exterior. No screen. Insect Screen - aluminum (18-14 mesh). Insect screen - aluminum (18-16 mesh). Bird screen - galvanized (1/2" x 19 GA.) Insect screen - stainless steel (18-16 mesh). Custom flanges (n/a for 24 hour). Stucco and glazing frame. Screen and frame - match louver. Frame only - match louver. Filter rack. Blankoff. <b>Burglar bars.</b>
	<b>ECD-745</b>	<b>TX</b>	-	<b>≤25 sq. ft.</b>	<b>≤50 sq. ft.</b>	Standard head and sill flashing. Net OD dimensions. Clip and continuous angles. Screen location - Front/exterior. No screen. Insect Screen - aluminum (18-14 mesh). Insect screen - aluminum (18-16 mesh). Bird screen - galvanized (1/2" x 19 GA.). Insect screen - stainless steel (18-16 mesh). Custom flanges (n/a for 24 hour). Stucco and glazing frame. Screen and frame - match louver. Filter rack. Blankoff. <b>Burglar bars.</b>
	<b>EBE-445, EBI-445</b>	<b>TX</b>	-	<b>≤25 sq. ft.</b>	<b>≤50 sq. ft.</b>	Integral flange frame (mechanically fastened only). Standard head and sill flashing. Net OD dimensions. Clip and continuous angles. Screen location - Front/exterior. No screen. Insect Screen - aluminum (18-14 mesh). Insect screen - aluminum (18-16 mesh). Bird screen - galvanized (1/2" x 19 GA.) Insect screen - stainless steel (18-16 mesh). Custom flanges (n/a for 24 hour). Stucco and glazing frame. Screen and frame - match louver. Frame only - match louver. Filter rack. Blankoff. <b>Burglar bars.</b>
	<b>EOD-445/637, EOJ-445/637 EXD-437/645, EXA-645</b>	<b>TX</b>	-	<b>≤25 sq. ft.</b>	<b>≤50 sq. ft.</b>	Stock actuators. Integral flange frame (mechanically fastened only). Standard head and sill flashing. Net OD dimensions. Clip and continuous angles. Jamb and blade seals. Screen location - Front/exterior. No screen. Insect Screen - aluminum (18-14 mesh). Insect screen - aluminum (18-16 mesh). Bird screen - galvanized (1/2" x 19 GA.) Insect screen - stainless steel (18-16 mesh). Custom flanges (n/a for 24 hour). Stucco and glazing frame. Screen and frame - match louver. Frame only - match louver. Filter rack. Blankoff. <b>Burglar bars.</b>
Standard paint extends the Quick Ship Program by 7 days	<b>EBV-145/445 (Catalog sizes only)</b>	<b>TX</b>	-	<b>49</b>	<b>150</b>	
<b>Access Doors</b> 	<b>HAD, CAD (Catalog sizes only)</b>	<b>CA, TX</b>	<b>10</b>	<b>25</b>	<b>100</b>	Standard latch quantities.
	<b>DM, DMR (Catalog sizes only)</b>	<b>CA, TX</b>	-	<b>20</b>		
	<b>DMHT-2300 (Catalog sizes only)</b>	<b>CA, TX</b>	-	<b>5</b>	<b>40</b>	

**NOTES:** \* Denotes single sections. 1/2 quantities are available for two sections. 1/3 quantities available for three sections.  
 Options and accessories shown in bold are only available on the 7-day program.  
 24 Hr, 3-Day and 7-Day Quick Ship: Orders received before 12 noon (central time) will ship the next business day, 3 days or 7 days respectively. Orders received after noon (central time) will ship in 2 days, 4 days or 8 days respectively.  
 Please contact Pottorff Customer Service at 817-509-2300 for special requirements.  
 Manufacturing location indicates CA-California or TX-Texas.  
 Revisions: 04/19